

DESIGNED WITH



TurboShield GT

Performance Enhancement for Gas Turbines

| Advanced-Technology Fine and (H)EPA Filters

Barrier Final Filters

MERV 15 (F9) – E10 Efficiency

Description

Purpose-built as secondary and final filters protecting gas turbines, diesel engines and other rotating equipment, TurboShield GT filters are designed for optimum filtration performance. Utilizing AAF's exclusive Impress® pleating technology, the TurboShield GT combines the best in filtration efficiency, low resistance, lifetime and mechanical stability into one package to deliver the best performance in its class.

Benefits

Low pressure drop

Optimum pleat geometry and media area as well as an unobstructed filter face minimize airflow restriction through the filter.

High efficiency

MERV 15/F9 – E10

Long service life

Low initial resistance, ideal pleat spacing and higher-than-average media density allow for maximized particle management and full media utilization.

Durable construction

Media is moisture-resistant and the media pack is encased in high-impact-plastic cell sides, which are corrosion-proof. Plastic protection screens on the upstream and downstream sides of the filter provide increased stability and protection. Impress pleat formation delivers a robust media pack with a burst strength exceeding industry standards.

Sealed media

The media pack is completely sealed in polyurethane on all four sides of the filter, keeping particulate from bypassing the filter media.

Leak-free seal


The seamless, foam-in-place gasket on the TurboShield GT eliminates particulate bypass around the filter frame.

Tested and proven

Tested to both North American ASHRAE 52.2-2012, European EN779 and EN1822 test protocols.

Moisture resistance

100% relative humidity protection. Vertical pleats provide moisture drainage. Intermittent glue separators allow coalesced water to drain down to the bottom of the filter.



1 | Patented Pleat Formation

2 | High Media Density

3 | High Burst Strength

Product features

- Sustained, high-particle-collection efficiency for maximum engine protection
- Low resistance to airflow, contributing to maintaining peak power output
- Mechanically stable pleat formation and support, so media resists distortion under high-pressure loads
- Ideal V-shape pleats for smooth airflow
- Corrosion-proof construction

Applications

- Coastal or high moisture applications
- Urban and industrial applications with heavy dust concentrations



BETTER AIR IS OUR BUSINESS®



GAS TURBINE SOLUTIONS

TurboShield GT

Performance Enhancement for Gas Turbines

| Advanced-Technology Fine and (H)EPA Filters

Barrier Final Filters

MERV 15 (F9) – E10 Efficiency


Efficiency	TurboShield GT F9 – MERV 15/F9 TurboShield GT E10 – E10
Initial Pressure	TurboShield GT F9 – 145 Pa (0.58" WG) TurboShield GT E10 – 225 Pa (0.90" WG) Tested at 2500 CFM / 4250 m ³ /hr
Recommended Final Resistance	2.55" WG / 635 Pa
Burst Strength	> 25" WG / 6225 Pa
Temperature	-40°C to + 80°C (-40°F to + 176°F)
Humidity Range	0 to 100% relative humidity

CONSTRUCTION


Filter Media	Specially formulated microfiberglass
Frame Material	Plastic
Protection Screen	Plastic
Adhesive	Polyurethane
Gasket	Seamless, foam-in-place

DIMENSIONS

Width	23.31" (592mm)
Height	23.31" (592mm)
Depth	11.5" (292mm)



RESISTANCE CURVE



Even pleat formation for low entry and exit losses



Seamless gasket for leak-free seal



1.855.583.HEPA (4372)
aafgtsolutions.com

ISO Certified Firm
©2014 AAF International MFAS-1-408 6/14

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

The USGBC Member logo is a trademark owned by the U.S. Green Building Council and is used by permission.

SALES OFFICES:

Europe & North Africa

AAF Ltd
Bassington Lane, Cramlington,
Northumberland NE23 8AF, UK
Tel: +44 1670 713 477
Fax: +44 1670 714 370

AAF International
Gas Turbine Division
Kreuzbergerstrasse 1
31226 Peine
Germany
Tel: +49 5171 294 80 14
Fax: +49 5171 294 80 15

AAF-SA
Rue William Dian,
B. P. 3
27620 Gasny
France
Tel: +33 2 32 53 60 60
Fax: +33 2 325 21917

AAF S.r.l.
Via Lario, 1
22070 Fenegrò (CO)
Italy
Tel: +39 031 35 25 311
Fax: +39 031 35 25 333

Middle East & Asia

AAF International
PO Box 28564
Dubai, UAE
Tel: +971 4 339 7688
Fax: +971 4 339 7881

AAF (Wuhan) Co. Ltd
268 CheCheng Road
Wuhan Economic & Technological
Development Zone
Wuhan, Hubei Province PR
China 430056
Tel: +86 27 84236698
Fax: +86 27 84236646

North & South America

AAF International Building
9920 Corporate Campus Drive,
Suite 2200
Louisville, KY 40223-5000, USA
Tel: +1 502 637 0408
Toll Free: 888 AAF 3596
Fax: +1 502 637 0147

AAF, S de RL de CV
Av. Primero de Mayo 85
San Andres Atenco
54040 Tlalnepantla
Estado de Mexico
Tel: +52 55 5565 5200
Fax: +52 55 5390 5814

U.S. Patent
No. 6,685,833 B2

